BEHR PREMIUM® Transparent Log Home Gloss Finish

- For Log & Timber Frame Homes, Siding, Fencing & Railings
- Easy Water Clean-Up
- UV Protection
- Mildew Resistant Finish

Must Prep Before Applying Finish

2 Coats Required

Spread Rate:
1st Coat 200-400 Sq. Ft.
2+ Coats 300-400 Sq. Ft.

Soap & Water Clean-Up

CAUTION: Finished surfaces may become slippery when wet.

WHERE TO USE

"For wood substrates only" Exterior wood surfaces such as: Log and Timber Frame Homes, Siding, Fencing and Railings. Do not use on horizontal surfaces subject to foot traffic.

PREPARATION †

(The following steps and products are required.) Use a product such as BEHR PREMIUM® NO. 64 Wood Stain & Finish Stripper to remove loose wood fibers, latex, oil-based and 100% acrylic coatings on new or weathered wood. BEHR PREMIUM NO. 63 All-In-One Wood Cleaner MUST be used following NO. 64 to clean, brighten & neutralize wood. When NO. 64 is not needed, use a product such as NO. 63 to clean and brighten the wood surface and to remove light to medium exterior stains caused by mold, mildew, algae & fungus. On new wood, use a product such as NO. 63 to remove mill glaze and open the pores of the wood. Rinse thoroughly and allow to dry before coating. Lightly sand to remove remaining wood fibers/fuzz.

APPLICATION

Must apply between 40-90° F (4.5-32° C). Do not use if rain is expected within 24 hours. The wood surface must be completely dry before application. Intermix multiple containers to ensure color uniformity. DO NOT THIN PRODUCT. Stir product occasionally throughout application. Test product for color on a small hidden area before proceeding. Use a 3/8" nap roller or nylon/polyester bristle brush. Airless sprayer with a .015 - .019" tip is recommended for experienced applicators only. Maintenance re-coating may be achieved by applying 2 coats at a spread rate of 200-400 sq. ft. (18-37 m²) per gallon over a clean, sound surface. Clean and recoat surface when finish no longer has gloss or luster or if the film is broken. Thoroughly seal the ends of the boards and all porous areas such as knots with several thin coats. Maintain a wet edge when applying. Back-brush during all application methods. Apply product end-to-end or to board lengths to prevent lap marks. Over application of finish will lead to surface failure including peeling and cracking. **Avoid applying finish too heavily. Two coats required, 3-4 coats recommended.** Avoid applying product in direct sunlight or on to hot surfaces.

WARRANTY

- Visit www.Behr.com for complete warranty information.

DRY TIME

Dries to touch in 8-12 hours. Recoat after 24 hours. Cool temperatures and/or high humidity will require additional drying time.

DISPOSAL

For disposal of empty containers and unused product contact your household refuse collection service.

† WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

A quality product that contains a mildewcide will assist in providing a finish that is resistant to mildew, provided that all existing mildew is removed prior to application. While this product does contain a mildewcide, it will not prevent mildew growth.

IMPORTANT! STORAGE AND DISPOSAL: DANGER! Rags, steel wool and waste soaked with this BEHR LOG HOME GLOSS FINISH may spontaneously catch fire if improperly discarded or stored. To avoid a spontaneous combustion fire, immediately after use, place rags, steel wool or waste in a sealed, water-filled, metal container. Do not store unused product inside the home. For disposal guidance, contact your household refuse collection service, fire department, county or state government environmental control agency.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: AN ALKYD RESIN. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15-20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.

To consult with a Behr Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

BEHR
A Masco Company

©2013 Behr Process Corporation
Santa Ana, CA 92704 U.S.A. • behr.com
V.O.C. (C.O.V.) <275 g/L • REV. 3/13